



Dungog Waste Management Facility

Waste Description

Asbestos Wastes are any wastes containing asbestos. (Asbestos waste is defined by the NSW Environmental Protection Authority (EPA) Waste Classification Guidelines). Asbestos wastes can be further classified into two groups:

1. Friable Asbestos is any material that contains asbestos and is in the form of a powder or can be crumbled, pulverized or reduced to powder by hand pressure when dry. Sprayed limpet, millboard, pipe and boiler lagging are examples of friable asbestos.
2. Bonded Asbestos Bonded asbestos material is any material that contains asbestos in a bonded matrix. eg. asbestos cement sheet ('fibro'), bituminous floor tiles/roof sheeting.

Health Hazards

Asbestos dust consists of tiny, resilient fibres almost indestructible fibres that can cause damage when they are inhaled into the lungs. The most dangerous fibres are the smallest ones which may be invisible to the naked eye, but which penetrate the lungs most deeply.

General Requirement for Asbestos

Due to the nature of the asbestos regulatory authorities impose conditions on its handling of the product. These authorities include Local Councils, the NSW EPA. Those authorities should be consulted prior to working with asbestos.

NSW EPA Waste Tracking NOTE:

The requirements below are specific to the receipt of asbestos waste at Dungog Waste Management Facility. In addition to those requirements, the NSW EPA has introduced requirements to track certain wastes, including asbestos. More information can be found on the EPA website <http://www.epa.nsw.gov.au/wasteregulation/transport-asbestos-tyres.htm>

All ASBESTOS LOADS in excess of 100kg and/or 10m² (whichever is less) must be registered with the NSW EPA.

Please register your loads via the EPA Integrated Waste Tracking System (IWTS) <https://kpmgorigins.com/iwts>



Requirement for disposal

NSW legislation (POEO (Waste) Regulation) requires that the waste hauler inform the landfill operator that the waste contains asbestos and sets out how the waste should be covered.

This Regulation also requires that asbestos waste in any form be unloaded '*in such a manner as to prevent the generation of dust or the stirring up of dust*'.

The following procedure for the disposal of asbestos wastes at [Dungog Waste Management Facility](#) is aimed at ensuring operations at the Facility comply with the requirements of this Regulation as well as those of other relevant legislation including the Workplace Health and Safety Act and Regulation.



Procedures for Disposal of Asbestos at Dungog Waste Management Facility

- Asbestos wastes must be booked-in by contacting the Dungog Waste Management Facility office on **4992 1634** before 3.30pm on the last weekday 48 hours prior to the delivery date. Booking details will include the type of asbestos waste, number and size of loads, source of the waste, contact details for the transporter and delivery date.

Note: Movement number required from Integrated Waste Tracking System IWTS for loads >100kg.

- Please note: Operational constraints limit the total amount of asbestos that can be received on a given day, and some asbestos loads must be assessed by Dungog Waste Facility staff prior to unloading. Hence, Facility management cannot guarantee that loads will be accepted on the desired day.
- Asbestos wastes must be delivered to DWMF between 8.30am and 12:00 midday on the day they are booking. **Asbestos wastes will not be received on weekends, public holidays or after 12:00pm midday on weekdays.**
- If rain events occur during the day or night leading up to the booking date, customers should contact the Waste Facility Office (**4992 1634**) prior to delivering their load to ensure that site conditions are suitable for asbestos disposal. Wet weather may make it unsafe for vehicles to cross the landfill.
- Asbestos waste loads will be directed to a designated area of the landfill. Vehicles delivering asbestos wastes should therefore be capable of safely traversing the landfill area which includes the tip face.
- Friable Asbestos waste must be double bagged in heavy duty bags made from low density polyethylene (LDPE) at least 0.2mm thick. Each bag will have maximum dimensions less than or equal to 1.2 m in height and 0.9 m in width and a maximum weight of 25 kg. Each bag must be marked 'CAUTION ASBESTOS' in letters of not less than 40 mm in height. These sealed bags must be placed on the ground in a manner which prevents their rupture. Should appropriately bagged asbestos be ripped or in any way expose asbestos following unloading, Waste Facility Staff will not be responsible for handling or re-bagging. The onus will be on the customer to ensure the asbestos is bagged to the requirements in the disposal process. Customers may be asked to safely reload if deemed appropriate by the Waste Facility team and come back again through rescheduling at another time. This may arise to ensure safety for staff, and all customers and to ensure continuity of operational services at the facility.



Disposal of Asbestos Waste – Procedure

- Bonded Asbestos waste must be presented for disposal and unloaded in a manner which avoids the creation of dust. Stabilised asbestos wastes can be presented as per the method for friable asbestos above. Where the friable asbestos method is not used, the following procedure will be acceptable:
- Thoroughly wet each individual sheet of asbestos waste at their source.
- Double wrap bundles of wetted sheets in heavy duty builder's-type plastic and seal individual bundles with heavy duty tape, such as duct tape. (The size of these bundles should be suited to the method of unloading - eg small enough to hand unload from a trailer).
- Present loads for inspection by landfill operational staff as directed by the weighbridge operator.
- Unload sealed bundles at the area identified by landfill staff in a manner which prevents the rupture of bundles. Again, should appropriately bagged asbestos be ripped or in any way expose asbestos following unloading, Waste Facility Staff will not be responsible for handling or re-bagging. The onus will be on the customer to ensure the asbestos is bagged to the requirements in the disposal process. Customers may be asked to safely reload if deemed appropriate by the Waste Facility team and come back again through rescheduling at another time. This may arise to ensure safety for staff, and all customers and to ensure continuity of operational services at the facility.

Note: It is the responsibility of transporters to deposit waste at the correct location and with bundles intact. The practice of 'running out' loads deposited by tip trucks will not be permitted.

Loads must be unloaded at the identified location to allow the wastes to be covered by operators without the need to first 'push-up' the asbestos waste. **If asbestos is placed in a truck, bin or similar that has been lined with plastic and then wrapped as a single bundle, the vehicle will not be permitted to unload.**



Non-Compliance with Required Procedures for Disposal

The potential health impacts associated with asbestos exposure and the clear legislative constraints for landfill operators mean that Facility management will not tolerate non-compliance with the above procedures for disposal of asbestos wastes.

Inappropriate Packaging of Waste

In the event that waste is deemed unable to be unloaded without rupturing following inspection by landfill operational staff, a supervisor will inspect the load. Should the supervisor also determine that the load cannot be unloaded in accordance with requirements, permission will not be granted to dispose of the material and the driver will be directed to leave the site.

Failure to Unload as per Requirements

Where loads are packaged as required but the method of unloading results in bundles rupturing, details of the vehicle and load will be recorded by the Facility and the customer reminded of the Centre's requirements. Should a second load be ruptured when unloading then no further asbestos loads will be accepted from that vehicle until it can be demonstrated that an alternative unloading method will be employed.

Charges

Please refer [Dungog Shire Councils](#) website for current disposal charges.

For asbestos waste loads that are mixed with other waste products, the entire load will be charged at the asbestos rate.

Note: Asbestos Loads should be delivered separately to other waste

To reduce the risk of asbestos contamination and exposure to our staff please, ensure the loads are compliant with this procedure so we can ensure the handling process is managed correctly.

Non-conformance to this procedure may lead to additional handling charges. Those charges may include costs to excavate and import additional soil to cover the asbestos, provision of water tanker etc.

Note: The Protection of the Environment Operations (Waste) Regulation 2014 makes it an offence to not comply with special requirements relating to asbestos waste as specified by the Regulation. Such an offence is liable to incur an infringement notice issued by authorised Dungog Shire Council or EPA officers.